


BUILDING REG APPROVAL CONDITIONS
 PROVIDED TO BS6841:2022
 - FIRE SAFETY SIGNAGE TO BE
 TO BE FITTED TO FIRE DOORS TO
 SMOKE APPROVED DOCUMENT B
 - FITTED TO ALL EXIT DOORS AND
 SATISFY APPROVED DOCUMENT B

NOTE:
 - TO NOT SCALE THIS DRG.
 - CONTRACTOR TO CHECK ALL
 IN CONTRACT ADMINISTRATION
 IN ORDER OF DISCREPANCIES
 - CONTRACTOR TO ALLOW FOR
 INSTALLATION WITH THEIR

CAFE
 LAY 40mm OF WHITE TILES AS
 AND CAP WITH TRIM OR
 BEVEL EDGE

DOOR
 - INSTALL FIRE DOOR WITH ALUMINUM
 DOOR CLOSURE LATCH TO FIRE ALARM
 IN GOOD QUALITY WHITE FINISH
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW
 - ASSET MECHANICAL CONTRACTOR
 TO PROVIDE AIR FLOW
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW

WEEKEND
 - INSTALL STANDING WORKTOP AT 900mm AS PER PLAN
 - MAKE GOOD ALL SURFACES AND SEAL WITH UNBLEND OR SIMILAR
 - INSTALL ALL SURFACES WITH QUALITY GLOSS PAINT
 - INSTALL ALL SURFACES WITH QUALITY GLOSS PAINT
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW
 - PROVIDE 100mm CLEARANCE UNDER
 DOOR TO PERMIT AIR FLOW



DATE	NO	BY	SCALE	NO	DATE	NO	DATE
PROJECT - BENCH BLOCKS BUILDING, 7/100 AUTHORITY DRAWN BY: [Signature] CHECKED BY: [Signature] DATE: 11/11/2022 SCALE: 1:50 SHEET NO: 1/1 TOTAL SHEETS: 1							



